Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK



0669

Accredited to ISO/IEC 17025:2017

Novatron Scientific Ltd

Issue No: 026 Issue date: 07 July 2022

Remarks

Novatron Scientific Ltd Contact: Mr S H Long
Novatron House Tel: +44 (0)1403 754416
46 London Road Fax: +44 (0)1403 754480

46 London Road Fax: +44 (0)1403 754480

Horsham E-Mail: simonhlong@btopenworld.com

West Sussex Website: www.novatron.co.uk

Calibration performed at the above address only

·

Calibration and Measurement Capability (CMC)

Measured QuantityRangeExpanded MeasurementInstrument or GaugeUncertainty (k = 2)

RH12 1AY

Instrument or Gauge		Uncertainty $(k = 2)$	
RELATIVE HUMIDITY Relative humidity meters	11 %rh to 50 %rh 50 %rh to 90 %rh for the temperature range 20 °C to 25 °C	1.7 %rh 2.0 %rh	Calibrations of devices with an electrical output may be undertaken. The accreditation covers other humidity units directly related to relative humidity, and
Saturated salt capsules	6 %rh 11 %rh 33 %rh 53 %rh 58 %rh 75 %rh 84 %rh 90 %rh 97 %rh 98 %rh	1.7 %rh 1.7 %rh 1.7 %rh 1.7 %rh 1.7 %rh 2.0 %rh 2.0 %rh 2.0 %rh 2.5 % rh 2.5 %rh	relative humidity, eg, equilibrium relative humidity (ERH).
TEMPERATURE Temperature sensors with	20 °C to 25 °C	0.20 °C	Calibrations of devices with an
indicators (measurements made in air)	20 0 10 20 0	0.20 0	electrical output may be undertaken.

END

Assessment Manager: PE



0669 Accredited to ISO/IEC 17025:2017

Schedule of Accreditation issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Novatron Scientific Ltd

Issue No: 026 Issue date: 07 July 2022

Calibration performed at main address only

Appendix - Calibration and Measurement Capabilities

Introduction

The definitive statement of the accreditation status of a calibration laboratory is the Accreditation Certificate and the associated Schedule of Accreditation. This Schedule of Accreditation is a critical document, as it defines the measurement capabilities, ranges and boundaries of the calibration activities for which the organisation holds accreditation.

Calibration and Measurement Capabilities (CMCs)

The capabilities provided by accredited calibration laboratories are described by the Calibration and Measurement Capability (CMC). which expresses the lowest measurement uncertainty that can be achieved during a calibration. If a particular device under calibration itself contributes significantly to the uncertainty (for example, if it has limited resolution or exhibits significant nonrepeatability) then the uncertainty quoted on a calibration certificate will be increased to account for such factors.

The CMC is normally used to describe the uncertainty that appears in an accredited calibration laboratory's schedule of accreditation and is the uncertainty for which the laboratory has been accredited using the procedure that was the subject of assessment. The measurement uncertainty is calculated according to the procedures given in the GUM and is normally stated as an expanded uncertainty at a coverage probability of 95 %, which usually requires the use of a coverage factor of k = 2. An accredited laboratory is not permitted to quote an uncertainty that is smaller than the published measurement uncertainty in certificates issued under its accreditation.

Expression of CMCs - symbols and units

It should be noted that the percentage symbol (%) represents the number 0.01. In cases where the measurement uncertainty is stated as a percentage, this is to be interpreted as meaning percentage of the measurand. Thus, for example, a measurement uncertainty of 1.5 % means $1.5 \times 0.01 \times q$, where q is the quantity value.

The notation Q[a, b] stands for the root-sum-square of the terms between brackets: Q[a, b] = $[a^2 + b^2]^{1/2}$

Assessment Management PE Page 2 of 2